Constant Power Point Source Array







Constant Power Point Source Array

VHD5

Introduction VHD5.0 - Mid High Module VHD8.10 - Low Mid Module VHD5.1 - Downfill VHD5 Amplification Transportation Wiring schematic Technical Specifications

A Bold New Advancement in Concert Sound Reinforcement

KV2 Audio's philosophy has always been to embrace the principles of point source speaker system design to provide optimum sound quality and coverage for applications and audiences of all sizes. The challenge for KV2 in building a large point source system for audiences of 50,000 people plus, was to reproduce the low mid energy that certain line arrays provide, through the summing of multiple drivers, whilst maintaining the key benefits of point source technology. These benefits include minimal destructive interference in the higher frequency range, accurate impulse response and superior sound.

Utilizing highly advanced point source speaker design, extremely efficient power management amplifier technology and totally unique hybrid signal processing, KV2 has created the first major advancement in large scale concert sound reinforcement since the development of the Line Array. The VHD5 Constant Power Point Source System is a true feat of engineering. Over five years in development it brings the benefits of point source technology to large-scale concert sound reinforcement. The system delivers audio over large areas with clarity and definition simply not achievable from the digitally processed line arrays that are so commonly used today.





Time-Shifts, Properties of Multi Point source

For some time now line arrays have been predominantly used for large concert sound systems. Having all components in a single axis array has solved certain issues in respect to comb filtering problems in the horizontal plane, but destructive interference still occurs from the multiple HF horns mounted vertically. The loss of high frequencies and cancellations through air disturbance caused



of the differences in distances to the listener from several Line array sources, each listener gets a blurred sound

Time-Shifts, Properties of Point source

At KV2 we believe that definition equals distance and the higher the reproduction quality of the source, the better the intelligibility over distance. The theory that line arrays have less losses over distance than point source is not only incorrect, but somewhat irrelevant if the sound is not intelligible at the back of the venue anyway. To achieve the high definition needed to cover long



by audience heat and wind is another major issue. Manufacturers have attempted to correct these problems in numerous ways both through acoustic design and DSP, however the end result has been further reductions in resolution, due to the limitations of digital sampling and the simple principles of physics that cannot be ignored.



distances we have focused on developing unique hybrid processing, which takes the very best available technologies in both the analogue and digital domains, advancing system design to a whole new level. The end result is ultimate resolution, Very High Definition sound, impulse accuracy and phase coherent audio arriving at the listening position, even over long distance.



To cover very large crowds you need a large system capable of delivering high SPL, running multiple components. To do this, as one large point source enclosure is somewhat difficult as it would be almost impossible to move around or transport.

With the VHD5.0 Constant Power Point Source Array, KV2 has focused on creating a modular system that has minimal destructive interference while utilising multiple components in a small number of cabinets. VHD 8.10 Low Mid Expansion Boxes are arrayed around the VHD5.0 Mid High Enclosure providing the extra headroom needed to deliver the low mids, keeping the sound balanced.

2kHz - 20kHz 400Hz - 2kHz 45Hz - 400Hz





High Frequency Horn

In essence the system is pieced together to represent one very large point source, each part of the system is proportional in size to the frequency wavelengths it reproduces. The radiated power of each bandwidth therefore remains consistent and balanced in relation to the overall frequency response. This ensures the same sound is delivered to every seat in the house.

The high frequency horn in the VHD5.0 combines three 3" NVPD (Nitrate Vapour Particle Deposition) Titanium Drivers on a special manifold horn with summing wave-guide. Delivering incredible output with extremely low distortion, this unique horn assembly provides crystal clear highs over distance with much higher resistance to air disturbances.

VHD5.0 - Mid High Module

The VHD5.0 is a three-way enclosure handling low mids, mids and highs over a frequency range from 45Hz through to 20kHz. It incorporates eight front-loaded ten inch low mid drivers, six horn-loaded eight inch mid range drivers and three 3" NVPD (Nitrate Vapour Particle Deposition) Titanium compression drivers on a custom designed, manifold horn assembly with summing waveguide. With the capacity to run full range down to 45Hz the VHD5.0 is usually crossed over at 70Hz to the VHD4.21 Active Sub Bass Modules. Both the VHD5.0 and VHD8.10 cabinets incorporate very simple to use integrated fly ware that links cabinets together quickly and easily. A complete system (4 VHD5.0's and 12 VHD8.10's) can be flown by two people in less than two hours.

VHD8.10 - Low Mid Module

When multiple low mid drivers are arrayed on a single axis they sum providing a considerable increase in the amount of low mid energy present and available in the 200Hz to 500Hz range. A lot more energy is needed in this area than in the higher frequency ranges so this summing effect helps deliver headroom in the system and keeps the overall sound balanced. To provide the required energy in the low mid, needed to cover very large audiences, KV2 developed the VHD8.10 Low Mid Expansion Box. This enclosure carries a further 8 front-loaded ten inch speakers and 3 of these cabinets are added to each VHD5.0. This provides a total of 32 ten inch speakers giving the extra headroom needed in the low mid band and extended projection of these frequencies over distance.

VHD5.1 - Downfill

VHD5.1 is a dedicated downfill enclosure, used with the VHD5 system for the largest events and audiences from 10,000 upwards, ensuring that all audience members enjoy a consistent experience venue wide without the need for delay systems. A 3-way design featuring a 3" high frequency compression driver with NPVD treated dome assembly; one horn loaded 8" mid range woofer featuring AIC technology and six front loaded 10" low mid woofers.





VHD4.21 Active Bass Module

The VHD4.21 Active Bass Module consists of two purpose designed Very High Definition enclosures, one active and one passive, each containing two custom designed 21" woofers. A Low Q design has been applied to attain the optimum speaker loading, enabling a high sensitivity of 109dB 1w/1 m. Running at close to 100% efficiency on any voltage from 160 to 270 Volts, the amplifier for the VHD4.21 is a revolution in electronic engineering, utilising a huge bank of capacitors as a power store.

This unique and innovative new power management system enables the onboard amplifier to deliver peak output levels of 14 kW, whilst operating at a modest constant power consumption of 3.5 kW from a 16 A circuit. The VHD4.21 Active Module represents proven KV2 Subwoofer Amplifer technology that has been consistently improved over the last decade to provide maximum control over the movement of large mass speakers. The end result is a fast, dynamic, Very High Definition subwoofer, truly capable of reproducing the articulation in a bass guitar, whilst also extending down to 28Hz.



VHD5 Amplification

The VHD5000 amplification and control unit is specifically designed to power the VHD5 loudspeaker system and contains two Class AB amplifiers totaling 900-watts for the high frequencies and a 1200-watt Class H amplifier for the mids. It also controls the VHD5000S which houses two 2500-watt Class G amplifiers that power the low mids in the system.

The VHD5000S is a rack mounted, high efficiency, low mid amplifier,

VHD5000 Master

Rack mounted active control and amplification unit specifically designed in conjunction with VHD5000S for powering the VHD5 loudspeaker system.

VHD5000S Slave

The VHD5000S is a rack mounted, high efficiency, low/mid amplifier, specifically designed in conjunction with VHD5000 for powering the VHD5.0 low/mid and VHD8.10 loudspeaker system.

VHD5100

Two channel, 3-way, active control and amplification system designed to independently control one VHD5.1 Downfill and an additional ESR215MkII fill loudspeaker.

Remote Control

A front panel touch screen allows easy muting and level adjustment of the frequency bands and full adjustment of the digital delay lines and other parameters on board. Control can also be done remotely via Ethernet or WiFi utilizing our proprietary K-NET networking. designed in conjunction with VHD5000 to power the VHD5 low mid loudspeaker system.

The VHD5100 is a two channel, 3-way, active control and amplification system designed to independently control one VHD5.1 Downfill and an additional ESR215MkII fill loudspeaker. It houses all signal processing and amplification, as well as providing a crossover function, if required, to add a fill channel subwoofer.





Transportation

The VHD 5.0 system is easily transportable using a fully locking dedicated heavy duty cart and further protected with strong padded durable nylon covers. The perfect size to load on a truck, with well balanced handles and an impressive size to weight ratio, the logistics of this system have been perfected with the same attention to detail as the exceptional audio reproduction, to guarantee a fast and efficient load in or out.





Extremely Durable Coating

Our answer to the strongest and most weather resistant paint finish KV2 has ever used. A unique chemical formula has been devised to create this extremely durable polyurethane coating, offering a seamless, flexible and impact resistant plastic protection to all wooden surfaces on the cabinet. The exceptional weatherproofing properties resist moisture intrusion, as well as cracking and peeling, whilst offering exceptional protection against U.V or exposure when used in areas of high humidity.





Wiring schematic



EXPLANATIONS:

Powercon (6-10)



Wiring schematic

Technical Specifications

System Acoustic Performance (VHD5.0 & VHD8.10)

Max SPL Long-term	147dB
Max SPL Peak	153dB
-3dB Response	70Hz to 20kHz
-10dB Response	45Hz to 22kHz
Full Range mode -3dB Response	50Hz to 20kHz
Crossover Point	70Hz, 400Hz, 2.0kHz
VHD5.0 Dimensions H/W/D	1125mm (44.29") x 1110mm (43.7") x 500mm
VHD8.10 Dimensions H/W/D	640mm (25.20") x 1110mm (43.7") x 500mm

Downfill (VHD5.1)

Max SPL Long-term	135dB
Max SPL Peak	138dB
-3dB Response	55Hz to 22kHz
-10dB Response	45Hz to 30kHz
Crossover Point	400Hz, 2.5kHz
Dimensions H/W/D	830mm (32.68") x 1110mm (43.7") x 350mm (

VHD5000

Number of Channels Rated Continuous Power Input Sensitivity Rack mountable Remote Control Operating Voltage

1 High Frequency 1 - 300W / High Fre. 2 - 600W / Mid Fr 1.55V RMS YES, 4RU K-NET, Ethernet 195V to 260V AC

VHD5100

Number of Channels Rated Continuous Power Input Sensitivity Rack mountable **Remote Control** Operating Voltage

2 (Fill + DownFill) High Frequency - 100W / Mid Fre. - 200W / Low Fre. - 1000W 1.55V RMS YES, 4RU K-NET, Ethernet 115V / 230V / 250V



EXPLANATIONS:

 Amphenol 6P / LK Link 8p - Mid-Hi speaker output
Amphenol 4P / LK Link 9P - Low-Mid speaker output
Amphenol 6P - Downfill speaker output (1x)
XLR - Subs

Ethernet CAT5

Ultra Low Frequency Section (VHD4.21)

Max SPL Long-term	147dB
Max SPL Peak	153dB
-3dB Response	34Hz to 180Hz
-10dB Response	28Hz to 240Hz
Crossover Point	60Hz to 120Hz
Dimensions H/W/D	700 mm (27.55″) x 1080 mm (42.52″) x 1200 mm (47.24″)

n (19.69″) (19.69")

(13.78″)

VHD5000S

	Number of Channels	2
re 1500W	Rated Continuous Power	Mid Bass Frequency - 2500W
	Input Sensitivity	1.0V RMS
	Rack mountable	YES, 4RU
	Rack Control	K-NET, Ethernet
	Operating Voltage	195V to 260V AC



VHD5 Product Overview video



VHD5 Rigging Tutorial video



Watch our product videos on **You Tube** . www.youtube.com/c/KV2Audiocom

